

❖ MODEL : INR-400POE



❖ FEATURE :

- ◆ Third-party IP cameras supported with ONVIF V2.4
- ◆ Build-in 4 CH PoE+(802.3at)
- ◆ Up to 300M long distance transmission of the PoE
- ◆ H.264 video & G.711 audio compression
- ◆ Up to 5 Megapixels resolution recording
- ◆ HDMI and VGA output up to 1920x1080P resolution
- ◆ Support 1 HDD (up to 6TB for per disk)
- ◆ Free Mobile/ PC client (Windows, Mac, iOS, Android)
- ◆ Support ONVIF & Various IP camera

❖ SPECIFICATIONS :

MODEL	INR-400POE
System	
Operating System	Embedded Linux®
Videos	
Video Compression	H.264/MJPEG
Video Input	4 CH
Recording Resolution	5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Live view / Playback	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Incoming Bandwidth	24 Mbps
Frame rate	Main stream: 50 fps (P) / 60 fps (N)} ; Sub-stream: 50 fps (P) / 60 fps (N)
Video output	2CH : 1 HDMI, 1 VGA
Play resolution	1920×1080P /60Hz, 1600×1200 /60Hz, 1280×1024 /60Hz, 1280×720 /60Hz, 1024×768 /60Hz
Audio	
Audio compression	G.711, Talkback : Yes
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
Audio output	1-ch, RCA (Linear, 1kΩ)
Network	
Ethernet	1 RJ45 port (10/100/1000 Mbps)
PoE	4 ports (IEEE802.3at)
USB	2 ports (1 Rear USB3.0, 1 Front USB2.0)
Protocol	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP*, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, ONVIF, Alarm Server, IP Search (Suggested to synchronize to external NTP server)
PC Client and Browser	ISS, IE6.0 and above, Google Chrome, Mozilla Firefox, Mac Safari
Mobile phone	Android, iOS
Web (IE)	Live Monitoring, Playback & System Configuration
Function	
OSD	Yes (Camera title, Time, Video loss, Camera lock, Motion detection, Recording...)
Decoding	Yes
Multiple-channel Playback	Yes
Search Mode	Time/Date, Alarm, VMD & Exact search (accurate to second), Smart search
Synchronous Playback	4 CH; Max. 4CH @1080P or 2CH @4MP
Internal HDD	1 SATA port; Up to 6TB for each disk
Alarm	1 in/ 1 out
Support IP Camera	ONVIF & Various IP camera
General	
Operating Humidity	0% - 90%
Operating Temperature	-10°C ~ +55°C
Power Consumption	60W (Fully Configured); 32W (Max. Power of PoE)
Power Supply	48 VDC
Dimension	43.6mm × 360.0mm × 254.3mm / (1.72"×14.17"×10.01"), 1U
Weight	1.5KG (without HDD)
Colors	Black