

PROFESSIONAL DVR

❖ MODEL : HDS-800E1M



❖ FEATURE :

- ◆ H.264 video & G.711 audio compression
- ◆ Compatible with Analog 960H/D1
- ◆ 8CH 720P AHD DVR, HDMI & VGA Video Out
- ◆ Video-playback, recording 720P@25/30FPS
- ◆ Support 1 HDD
- ◆ HDMI and VGA output up to 1080HD resolution
- ◆ Support browser IE 6.0 Above
- ◆ Free ISS Management software and DDNS server
- ◆ Free Mobile (IOS, Android)

❖ SPECIFICATIONS :

MODEL	HDS-800E1M
System	
Operating System	Embedded Linux®
Videos	
Video System	NTSC/PAL Switch Selectable
Video Compression	H.264/MJPEG
Video Input	8CH
Recording Resolution	8CH @720P ; 4CH @720P + 4CH @960H ; 8CH @960H
Record Frame rate	PAL: 8CH 720P@25fps, NTSC: 8CH 720P@30fps
Recording Quality	Worst, Worse, Bad, Normal, Better, Best
Video output	1 HDMI, 1 VGA
CVBS output	NTSC:720*480
Audio	
Audio compression	G.711, Talkback : Yes
Audio input/ output	4 in/ 1 out
Network	
Ethernet	1 RJ45 port (10/100/1000 Mbps)
USB	2 ports * USB2.0
3G/ Wifi External Module	Yes, with USB 2.0 Port, 100Meters
GUI INTERFACE	Supported GUI 16 Bit True Color
PTZ Protocol	PELCO-D, PELCO-P, etc 17 kinds of protocol
Network Service	TCP/IP, PPPOE, DDNS, FPT, NTP, UPNP
PC Client and Browser	ISS, IE6.0 and above
Mobile phone	Android, iOS
Web (IE)	Live Monitoring, Playback & System Configuration
Function	
OSD	Yes (Camera title, Time, Video loss, Camera lock, Motion detection, Recording...)
Remote Operation	Remote view, remote playback, remote setup
Backup	Yes, with USB 2.0 Port/ Network Back up ; File Format : Avi
Division/ Sync Playback	Yes
Multiple-channel Playback	Yes
Search Mode	Time/Date, Alarm, VMD & Exact search (accurate to second), Smart search
Internal HDD	1 SATA port
Zoom	Preview & Playback , Zoom Support
General	
RS-485	01
Operating Humidity	0% - 90%
Operating Temperature	-10°C ~ +55°C
Power Consumption	<6W (Exclude HDD)
Power Supply	12 VDC ,2A
Dimension	260mm × 44mm × 221mm
Colors	Black